

TECHNICAL DATA SHEET



CABLE STEP COVER, P/N 101-100 OPENING TOP ESD-safe cable cover

Engineered for ESD-sensitive areas. The Cable Step Cover combines a hinged diamond-tread top with a powder-coated steel frame and leveling ESD conductive feet, integrating with conductive flooring to help control static.

KEY FEATURES

ESD-aware design:	Integrates with conductive flooring to help maintain a controlled resistance-to-ground path
Anti-slip tread:	Diamond-plate tread top surface for confident footing in lab environments
Safety aware design:	Folded perimeter reduces hazard points
Rigid steel frame:	Powder-coated structure engineered for durability
Leveling stability:	Conductive technopolymer leveling feet help stabilize on uneven floors while supporting ESD control
High load capacity:	312 lb maximum load with safety factor
Field-replaceable components:	Leveling feet may be easily replaced



TECHNICAL DATA

Dimensions:	24 in x 36 in x 9.5 in (609.6 mm x 914.4 mm x 241.3 mm)
Weight:	29 lb (13.15 kg)
Top surface:	1/16th Aluminum diamond-tread plate
Mechanism:	Gas Strut
Frame:	Steel tubing; powder-coated
Frame-to-foot conductivity:	Less than 2 Ω resistance
Leveling foot conductivity:	Surface resistivity = $10^9 \Omega$ (ASTM D991 measuring method) Volume resistivity = $10^9 \Omega\text{cm}$ (ASTM D991 measuring method)
Max load:	312 lb maximum recommended load with safety factor

TECHNICAL DATA SHEET



CABLE STEP COVER, P/N 101-100 OPENING TOP ESD-safe cable cover

APPLICATIONS

Ideal for use in environments where electrostatic discharge (ESD) control is critical.

Key applications include:

- Aerospace & Defense
- Electronics Manufacturing
- Testing Labs
- Cleanrooms
- Controlled Environments
- Semiconductor
- Medical Device Manufacturing
- ESD-Sensitive Settings

Suitable for any facility requiring robust ESD protection.

*Custom variations available.

ORDERING INFORMATION

SKU: (standard) 101-100 — Cable Step Cover Opening Top Included: assembled frame, diamond-plate top, conductive leveling feet

Options / variants (quote as needed):	• Top material/finish: aluminum (standard) or stainless steel; alternate textures/finishes • Color: standard blue; custom colors available • Footing: conductive leveling feet (standard); alternative foot types upon request • Documentation: serialization, inspection report
--	--

NOTES

- ESD: Unit is designed to be part of an ESD-control system; performance depends on proper installation, conductive flooring, and facility grounding practices. Verify resistance-to-ground per your site standard before use.
- Customization: Dimensions, finishes, and hardware can be tailored to your workflow—contact sales for engineered-to order variants.